

# Listings & Approvals

## BUR/Modified Bitumen Membrane Systems

---

### TGIK

#### Roofing Systems, Uplift Resistance

**T. Clear Corp, Hamilton, OH 45015**

**R14358(N)**

BUR/Modified Bitumen Membrane Systems

**Uplift Resistance:** 135 psf.

**Deck:** Steel, min. 22 MSG.

**Gypsum Board:** 5/8 in. thick min. mechanically fastened

**Fasteners:** No. 12-12 by 1 5/8 in. long, No. 3 Phillips drive truss head types point steel screws. A 3 in. diameter, No. 22 MSG Steel Pressure Plate used with each screw. A total of 18 screws used per 4 by 8 ft. sheet. Positioned in 3 rows. Rows located 6 in. from 8 ft. sides and along the center line. Fasteners spaced 18 in. OC beginning 3 in. from the 4 ft. edge.

**Base/Ply Sheet:** One or more layers of Type G1, Type G2, or UL Classified polyester base/ply sheet hot-mopped to the gypsum board.

**Surfacing:** LightGUARD® Panels, min. 2 in. thick.

**Strapping:** No. 22 MSG thick, 3 in. wide, coated or stainless steel. Fastened to peripheral LightGUARD Panels with blind rivet type fasteners. Minimum 2 fasteners used per unit.

666789001

Underwriter's Laboratories Inc.®

011/0242937 172

®LightGUARD is a registered trademark of the T. Clear Corporation

TCC-L-FA-95-A

