

# Listings & Approvals

## Coal Tar Pitch Felt Systems With Hot Roofing Coal Tar Pitch

T. Clear Corp, Hamilton, OH 45015

R14358(N)

Class A

Coal Tar Pitch Felt Systems with Hot Roofing Coal Tar Pitch

1. Deck: C-15/32

Incline: 1

**Base Sheet:** Required for combustible decks– asphalt organic, asbestos or inorganic glass, nailed.

**Ply Sheet:** Two or more layers Type 15 asphalt organic, asbestos or Type G1 inorganic glass, coal tar pitch, or bitumen. 25 lbs./sq. sealed with coal tar pitch or bitumen. 25 lbs./sq. followed by coal tar at 45 lbs./sq.

**Insulation:** Dow Chemical Styrofoam RM, PC, or Styrorib (plastic) 1 in. minimum with or without attachment.

**Scrim:** (Optional) "Fabrene", International Paper D689" or "Rufon Polypropylene". 2 oz./sq. yd.

**Surfacing:** Crushed stone, river bottom stone (3/4 to 1 3/4 in. diameter). 900 lbs./sq. concrete blocks, 10 lbs./sq. minimum spread not more than 1/8 in. apart, or LightGUARD® panels surfaced with 5/16 in. minimum concrete mortar, butted together.

2. Deck: C-15/32

Incline: 2

**Base Sheet:** Required for combustible decks– Type 15 asphalt inorganic felt, nailed.

**Ply Sheet:** Two or more layers Type 15 asphalt organic, asbestos or Type G1 inorganic glass felt secured with hot roofing asphalt.

**Insulation:** Dow Chemical Styrofoam RM, PD, or Styrorib (plastic) 1 in. minimum.

**Scrim:** (Optional) "Fabrene", International Paper D689" or "Rufon Polypropylene". 2 oz./sq. yd.

**Surfacing:** Crushed stone, river bottom stone (3/4 to 1 3/4 in. diameter). 900 lbs./sq. concrete blocks, 10 lbs./sq. minimum spread not more than 1/8 in. apart, or LightGUARD® panels surfaced with 5/16 in. minimum concrete mortar, butted together.

®LightGUARD is a registered trademark of the T. Clear Corporation

