

# Listings & Approvals

## Single-Ply Membrane Systems

---

**T. Clear Corp, Hamilton, OH 45015**

**R14358(N)**

**Class A - Ballasted**

Single-Ply Membrane Systems

**1. Deck:** C-15/32

**Incline:** 3

**Membrane:** Any UL Classified PVC, EPDM, CPE, TRE, nitrile alloy or modified bitumen, loose laid or mechanically fastened.

**Slip Sheet:** (Optional) Dry inorganic glass fiber mat.

**Insulation:** Dow Chemical Styrofoam RM, PD, SM, TG, Grayboard, or Styrorib (plastic), 1 in. minimum

**As an alternative, the membrane may be loose laid over the insulation**

**Scrim:** (Optional) "Fabrene", "International Paper D689" or "Rufon Polypropylene". 2 oz./sq. yd.

**Surfacing:** Crushed stone, river bottom stone (3/4 tp 1 3/4 in. diameter). 900 lbs./sq. concrete blocks, 10 lbs./sq. minimum spread not more than 1/8 in. apart, or LightGUARD® panels surfaced with 5/16 in. minimum concrete mortar, butted together.

®LightGUARD is a registered trademark of the T. Clear Corporation

Underwriter's Laboratories Inc.®

