

List of Approved Deck/Membrane Assemblies Acceptable to T. Clear Corp.

(See Specifications for Details)

Deck Type	Metal Deck	Monolithic Concrete	Panel Concrete	Wood Deck	Wood Fiber	Insulated Concrete	Existing System
Membranes	Fully-Adhered						
Fiber-glass B.U.R.	Approved S-BA-3-AD	Approved C-BA-3-AD	Approved P-BA-3-AD	No	Approved F-BA-3-AD	No	No
Modified Bitumen	Approved S-MB-2-AD	Approved C-MB-1-AD	Approved P-MB-2-AD	No	Approved F-MB-2-AD	No	No
Single-Ply	Approved S-TS(P)-1-AD	Approved C-TS(P)-1-AD	Approved P-TS(P)-1-AD	No	Approved F-TS(P)-1-AD	No	No
	Mechanically Attached (T. Clear Air Barrier Criteria Must be Incorporated)						
Fiber-glass B.U.R.	Approved S-BA-3-MA	No	No	Approved W-BA-3-MA	Approved F-BA-3-MA	Approved I-BA-3-MA	Approved E-BA-3-MA
Modified Bitumen	Approved S-MB-2-MA	No	No	Approved W-MB-2-MA	Approved F-MB-2-MA	Approved I-MB-2-MA	Approved E-MB-2-MA
Single-Ply	Approved S-TS(P)-1-MA	No	No	Approved W-TS(P)-1-MA	Approved F-TS(P)-1-MA	Approved I-TS(P)-1-MA	Approved E-TS(P)-1-MA
	Loose-Laid (T. Clear Air Barrier Criteria Must be Incorporated)						
Single-Ply	Approved S-TS(P)-1-LL	Approved C-MB-TS(P)-1-LL	Approved P-TS(P)-1-LL	Approved W-TS(P)-1-LL	Approved F-TS(P)-1-LL	Approved I-TS(P)-1-LL	Approved E-TS(P)-1-LL

Roof Membrane Identification Codes

Deck Type	Membrane Type	No. Plys	Means of Attachment
S=Steel	BA=Asphalt BUR	1	MA=Mechanically-Attached
I=Insulated Concrete	BC=Coal Tar Pitch BUR	2	
G=Gypsum	MB=Modified Bitumen	3	AD=Adhered
W=Wood & Plywood	TS=Thermoset Membrane	4	LL=Loose-Laid
F=Wood Fiber	TP=Thermoplastic Membrane		
P=Pre-Cast Concrete	HA=Hot-Applied Liquid		
C=Concrete Poured			
E=Existing System			

Example: S=Steel, BA=Asphalt BUR, 3=3 Ply, AD=Adhered **S-BA-3-AD**